Click on THIS PAGE to return to preservative-treated wood information at InspectAPedia.com

MATERIAL SA	FETY
DATA SHEE	Т

Emergency Contact Information:

PRODUCT NAME: Wolmanized® L3 Outdoor® Wood

1. PRODUCT AND COMPANY IDENTIFICATION

REVISION DATE: 04/10/2007 Manufactured by:

SUPERCEDES:

MSDS Number: 000000002628

Wolman® AG Treated Wood SYNONYMS:

CHEMICAL FAMILY:

DESCRIPTION / USE: **Treated Wood Products** FORMULA: None established

2. HAZARDS IDENTIFICATION

Wood dust is classified as: carcinogenic, possible sensitizer, mild skin OSHA Hazard Classification: irritant, possible respiratory irritant.

Routes of Entry: Inhalation, skin, eyes, ingestion Chemical Interactions: No known or reported interactions.

Medical Conditions Aggravated: Inhalation of the dust from this material at concentrations above

> the TLV can aggravate pre-existing upper respiratory and lung diseases such as bronchitis, emphysema and asthma., Skin

diseases including eczema and sensitization

Human Threshold Response Data

Odor Threshold Not established for product.

Not established for product. Irritation Threshold

Hazardous Materials Identification System / National Fire Protection Association Classifications

Flammability Hazard Ratings: Health Physical / Instability PPI / Special hazard.

HMIS 3* 0 1

NFPA Not established

Immediate (Acute) Health Effects

Inhalation Toxicity: Airborne treated or untreated wood dust may cause nose, throat or lung

irritation.

Skin Toxicity: Handling of wood may result in skin exposure to splinters. Prolonged

and/or repeated contact with treated or untreated wood dust may result

in mild irritation.

Treated or untreated wood dust may cause mechanical irritation. Eye Toxicity:

Wolmanized® L3 Outdoor® Wood

REVISION DATE: 04/10/2007 Page 1 of 10

Ingestion Toxicity: Not expected to be a route of exposure in normal industrial use.

Acute Target Organ Toxicity: Skin, Eyes, Respiratory Tract

Prolonged (Chronic) Health Effects

IARC has classified untreated hardwood and hardwood/softwood mix Carcinogenicity:

wood dust as a Group 1 human carcinogen. The wood dust

classification is based primarily on IARC's evaluation of increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with occupational exposures to untreated wood dust.

NTP has classified all untreated wood dust as a carcinogen.

Reproductive and

Not known or reported to cause reproductive or developmental toxicity.

Developmental Toxicity:

Inhalation: May cause respiratory sensitization and/or irritation.

Treated or untreated wood dust, depending on the species, may cause Skin Contact:

dermatitis on prolonged, repetitive contact.

Not expected to be a route of exposure in normal industrial use. Ingestion:

Various species of untreated wood dust can elicit an allergic respiratory Sensitization:

response in sensitized persons. Various species of untreated wood dust

can elicit an allergic type skin irritation in sensitized persons.

Chronic Target Organ Toxicity:

Supplemental Health Hazard

Respiratory Tract, Skin, Eyes No additional health information available.

Information:

3. COMPOSITION / INFORMATION ON INGREDIENTS

CAS OR CHEMICAL NAME	CAS#	<u>% RANGE</u>
Propanol, (2,methoxy-methylethoxy-)	34590-94-8	
PEG-40 Castor Oil	61791-12-6	
Propiconazole	60207-90-1	
TEBUCONAZOLE	107534-96-3	
Imidacloprid	138261-41-3	
Wood Dust	Not Assigned >=	98 -
Formaldehyde	50-00-0 (Only applies to plywood products)	0 - 0.1

Wolmanized® L3 Outdoor® Wood

REVISION DATE: 04/10/2007 Page 2 of 10

4. FIRST AID MEASURES

Inhalation: IF INHALED: Remove individual to fresh air. Seek medical attention if breathing

becomes difficult or if respiratory irritation develops. If not breathing, give artificial

respiration. Call for medical assistance.

Skin Contact: IF ON SKIN: Flush skin with water for 15 minutes. Take off all contaminated

clothing. Seek medical attention if irritation develops.

Eye Contact: IF IN EYES: Flush eyes with plenty of water for at least 15 minutes. Seek medical

attention if irritation develops.

Ingestion: IF SWALLOWED: Immediately drink water to dilute. Seek medical attention if

symptoms develop. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Flammability Summary (OSHA): Product is not known to be flammable, combustible, pyrophoric or

explosive.

Flammable Properties

Flash Point: No data.

Autoignition Temperature: No data.

Fire / Explosion Hazards: Combustible solid If the product is involved in a fire, toxic smokes

could develop. Dust may be ignitable if mixed with air in the

presence of an ignition source.

Extinguishing Media: Water spray

Fire Fighting Instructions: In case of fire, use normal fire-fighting equipment and the personal

protective equipment recommended in Section 8 to include a NIOSH

approved self-contained breathing apparatus.

Hazardous Combustion Products: During a fire, irritating and highly toxic gases may be generated by

thermal decomposition or combustion.

Upper Flammable / Explosive Limit, % in air: No data. Lower Flammable / Explosive Limit, % in air: No data.

6. ACCIDENTAL RELEASE MEASURES

Personal Protection for Emergency

Situations:

Additional protective clothing must be worn to prevent personal contact with this material. Those items include but are not limited to

boots, impervious gloves, hard hat, splash-proof goggles,

impervious clothing, i.e., chemically impermeable suit, self-contained

breathing apparatus.

Spill Mitigation Procedures

Air Release: Not applicable

Water Release: Notify all downstream users of possible contamination.

Land Release: Contain all solids for treatment or disposal.

Additional Spill Information: Remove all sources of ignition. Dispose of spill residues per

guidelines under Section 13, Disposal Consideration.

Wolmanized® L3 Outdoor® Wood

REVISION DATE: 04/10/2007 Page 3 of 10

7. HANDLING AND STORAGE

Handling: DO NOT BURN TREATED WOOD. Do not use pressure treated

chips or sawdust as mulch. Whenever possible, sawing or

machining treated or untreated wood should be performed outdoors to avoid accumulations of airborne wood dust. Wash hands

thoroughly before eating, drinking, using tobacco products, and/or

using restrooms.

Storage: Keep away from unguarded flame, sparks, and heat sources.

Protect from physical damage. Maintain good housekeeping.

Incompatible Materials for Storage: strong acids oxidizers

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Whenever possible, sawing or machining treated or untreated wood should

be performed outdoors or in well ventilated areas to avoid accumulations of airborne wood dust. Ventilation should be sufficient to maintain exposures

below the recommended exposure limits.

Protective Equipment for Routine Use of Product

Respiratory Protection: When sawing or cutting treated or untreated wood, wear a NIOSH approved

P95 or P100 Particulate filter respirator. FOR PLYWOOD PRODUCTS ONLY: If Formaldehyde vapor levels exceed the recommended exposure

limits, wearing a NIOSH approved respirator is required.

Respirator Type: For plywood products only: A NIOSH approved full-face air purifying

respirator with combination formaldehyde/organic vapor cartridge and a P100 filter. Air purifying respirators should not be used in oxygen deficient or IDLH atmospheres or if exposure concentrations exceed ten (10) times

the published limit.

Skin Protection: Wear leather gloves. Wear long sleeve shirt, pants, and steel-toed shoes

when handling treated or untreated wood.

Eye Protection: Use safety glasses with side shields or chemical goggles when sawing or

cutting treated or untreated wood.

Protective Clothing Type: Wear leather gloves.

Exposure Limit Data

CHEMICAL NAME Propanol, (2,methoxy- methylethoxy-)	<u>CAS #</u> 34590-94-8	Name of Limit ACGIH	<u>Exposure</u> 100 ppm TWA
Propanol, (2,methoxy- methylethoxy-)	34590-94-8	ACGIH	150 ppm STEL
Propanol, (2,methoxy- methylethoxy-)	34590-94-8	ACGIH	Skin designation: Can be absorbed through the skin.
Propanol, (2,methoxy-methylethoxy-)	34590-94-8	OSHA Z1	100 ppm PEL 600 mg/m3 PEL
Propanol, (2,methoxy-methylethoxy-)	34590-94-8	OSHA Z1	Skin designation: Can be absorbed through the skin.
Propanol, (2,methoxy-methylethoxy-)	34590-94-8	NIOSH-IDLH	600 ppm

Wolmanized® L3 Outdoor® Wood

REVISION DATE: 04/10/2007 Page 4 of 10

1			
Wood Dust		OSHA Z1	15.0 mg/m3 PEL Total dust.A state-run OSHA program may have more stringent limits for wood dust and/or PNOR.
Wood Dust		OSHA Z1	5.0 mg/m3 PEL Respirable fraction.A state-run OSHA program may have more stringent limits for wood dust and/or PNOR.
Wood Dust		ACGIH	1.0 mg/m3 TWA Inhalable fraction.(Western Red Cedar)
Wood Dust		ACGIH	1.0 mg/m3 TWA Inhalable fraction.(All other species)
Formaldehyde	50-00-0	ACGIH	0.3 ppm Ceiling(Only applies to plywood products.)
Formaldehyde	50-00-0	OSHA	Reference: (Only applies to plywood products.)
Formaldehyde	50-00-0	OSHA	0.75 ppm TWA(Only applies to plywood products.)
Formaldehyde	50-00-0	OSHA	2 ppm STEL(Only applies to plywood products.)
Formaldehyde	50-00-0	OSHA	0.5 ppm OSHA_ACT(Only applies to plywood products.)
Formaldehyde	50-00-0	NIOSH-IDLH	20 ppm (Only applies to plywood products.)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: solid Form solid

Color: Varies depending on colorant used

Odor: None

Molecular Weight: None established Specific Gravity: Not applicable Not applicable pH: Boiling Point: Not applicable Freezing Point: Not applicable Melting Point: No data

Density: solid Vapor Pressure: Not applicable Vapor Density: Not applicable Viscosity: Not applicable Fat Solubility: No data No data.

Solubility in Water:

Wolmanized® L3 Outdoor® Wood

REVISION DATE: 04/10/2007 Page 5 of 10

Partition coefficient n-

No data

No data

octanol/water:

Evaporation Rate:

No data

Oxidizing:

None established

Volatiles, % by vol.: No data VOC Content **HAP Content** No data

10. STABILITY AND REACTIVITY

Stability and Reactivity Summary: Stable under normal conditions. Product will not undergo

hazardous polymerization.

Conditions to Avoid: Sparks, open flame, other ignition sources, and elevated

temperatures., Contact with incompatible substances

Chemical Incompatibility: strong acids, oxidizers

Hazardous Decomposition Products: During a fire, irritating and highly toxic gases may be generated by

thermal decomposition or combustion.

Decomposition Temperature: No data

11. TOXICOLOGICAL INFORMATION

Component Animal Toxicology

Oral LD50 value:

Propanol, (2,methoxy-LD50 = 5,300 mg/kg

methylethoxy-) PEG-40 Castor Oil

LD50 > 5,000 mg/kgRat LD50 = 1,517 mg/kgRat

Propiconazole **TEBUCONAZOLE** LD50 = 1,700 mg/kgRat Male TEBUCONAZOLE LD50 = 4,000 mg/kg Rat Female

Imidacloprid LD50 = 450 mg/kg Rat

Dermal LD50 value:

Propanol, (2, methoxy-LD50 $> 2,000 \, \text{mg/kg}$ Rabbit

methylethoxy-)

PEG-40 Castor Oil LD50 Believed to be > 2,000 mg/kg Rabbit

Propiconazole LD50 $> 4,000 \, \text{mg/kg}$ Rat **TEBUCONAZOLE** LD50 > 5,000 mg/kgRat Imidacloprid LD50 > 5,000 mg/kgRabbit

Inhalation LC50 value:

Propanol, (2, methoxy-Inhalation LC50 1 HOUR > 200 MG/L Rat

methylethoxy-) PEG-40 Castor Oil

Inhalation LC50 Believed to be > 2.0 MG/L Rat

Propiconazole Inhalation LC50 4 HOUR > 5.27 MG/L Rat **TEBUCONAZOLE** Inhalation LC50 4 HOUR > 5 MG/L Rat Imidacloprid Inhalation LC50 4 HOUR > 5.3 MG/L Rat

Product Animal Toxicity

Oral LD50 value: LD50 Believed to be > 5,000 mg/kg Dermal LD50 value: LD50 Believed to be > 2,000 mg/kg Rabbit

Inhalation LC50 No data

value:

Wolmanized® L3 Outdoor® Wood

REVISION DATE: 04/10/2007 Page 6 of 10

Skin Irritation: Prolonged and/or repeated contact with treated or untreated wood dust may result

in mild irritation.

Eye Irritation: Treated or untreated wood dust may cause mechanical irritation.

Skin Sensitization: Various species of untreated wood dust can elicit an allergic respiratory response

in sensitized persons., Various species of untreated wood dust can elicit an

allergic type skin irritation in sensitized persons.

Subchronic / Chronic

Toxicity:

May cause respiratory sensitization and/or irritation., Treated or untreated wood dust, depending on the species, may cause dermatitis on prolonged, repetitive

contact.

PEG-40 Castor Oil There are no known or reported effects from chronic

exposure.

Reproductive and

Developmental Toxicity:

PEG-40 Castor Oil

Not known or reported to cause reproductive or developmental toxicity.

This material has been tested in laboratory animals and

no evidence of teratogenicity or embryotoxicity was

seen.

Propiconazole This chemical has been tested in laboratory animals

and there was no evidence of reproductive toxicity,

teratogenicity, or developmental toxicity.

Mutagenicity: Not known or reported to be mutagenic.

Propanol, (2,methoxy-methylethoxy-) Not known or reported to be mutagenic.

PEG-40 Castor Oil

This material was non-mutagenic in the Ames test.

This chemical has been tested in a battery of

mutagenicity/genotoxicity assays and the results were

negative.

Carcinogenicity: IARC has classified untreated hardwood and hardwood/softwood mix wood

dust as a Group 1 human carcinogen. The wood dust classification is based

primarily on IARC's evaluation of increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with occupational exposures to untreated wood dust. NTP has classified all

untreated wood dust as a carcinogen.

Propanol, (2,methoxy-methylethoxy-)

This chemical is not known or reported to be

carcinogenic by any reference source including IARC,

OSHA, NTP, or EPA.

PEG-40 Castor Oil This material did not cause cancer in long-term animal

studies.

Propiconazole This material has been classified by the U.S. EPA as a

"Group C" Carcinogen (Suggestive Human Carcinogen), based on the observation of tumors in mouse livers. The

relevance of tumors in the mouse liver has been questioned when assessing the risk to humans.

TEBUCONAZOLE This material has been classified by the U.S. EPA as a

"Group C" Carcinogen (Suggestive Human Carcinogen), based on the observation of tumors in mouse livers. The

relevance of tumors in the mouse liver has been questioned when assessing the risk to humans.

Wolmanized® L3 Outdoor® Wood REVISION DATE: 04/10/2007

Page 7 of 10

12. ECOLOGICAL INFORMATION

Overview: No data for product. Individual constituents are as follows:

Ecological Toxicity Values for: Propanol, (2,methoxy-methylethoxy-)

Fathead minnow (Pimephales - 96 HOUR LC50 > 10,000 mgl

promelas),

Daphnia magna, - 48 HOUR EC50 1,919 mgl

Ecological Toxicity Values for: Propiconazole

Carp, - 96 HOUR LC50 6.8 mgl

Rainbow trout (Salmo gairdneri), - 96 HOUR LC50 5.3 mgl

Crayfish - 96 HOUR LC50= 42 mgl

Daphnia magna, - 48 HOUR EC50= 4.8 - 11.5 mg/l

Ecological Toxicity Values for: Imidacloprid

Carp, - 96 HOUR LC50 = 280 mgl

Rainbow trout (Salmo gairdneri), - 96 HOUR LC50 = 211 mgl

Daphnia magna, - 48 HOUR EC50= 85 mgl

13. DISPOSAL CONSIDERATIONS

CARE MUST BE TAKEN TO PREVENT ENVIRONMENTAL CONTAMINATION FROM THE USE OF THE MATERIAL. THE USER OF THE MATERIAL HAS THE RESPONSIBILITY TO DISPOSE OF UNUSED MATERIAL, RESIDUES AND CONTAINERS IN COMPLIANCE WITH ALL RELEVANT LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS REGARDING TREATMENT, STORAGE AND DISPOSAL FOR HAZARDOUS AND NONHAZARDOUS WASTES.

Waste Disposal Summary: If this product becomes a waste, it will be a nonhazardous waste

according to U.S. RCRA regulations. Dispose of in accordance with all Local, State, Federal, and Provincial Environmental Regulations.

Disposal Methods: Dispose of in a permitted industrial waste landfill following Federal,

State Local, or Provincial regulations.

Potential US EPA Waste Codes: Not applicable

14. TRANSPORT INFORMATION

Land (US DOT): NOT REGULATED AS A DOT HAZARDOUS MATERIAL Water (IMDG): NOT REGULATED AS A HAZARDOUS MATERIAL,

Flash Point: No data.

Air (IATA): NOT REGULATED AS A HAZARDOUS MATERIAL,

Emergency Response Guide Number: Not applicable

Wolmanized® L3 Outdoor® Wood

REVISION DATE: 04/10/2007 Page 8 of 10

15. REGULATORY INFORMATION

UNITED STATES:

Toxic Substances Control Act (TSCA): This item is exempt from TSCA and FIFRA under the treated

article exemption per 40 CFR 152.25(a).

EPA Pesticide Registration Number: None established

FIFRA Listing of Pesticide Chemicals Not registered in the US under FIFRA.

(40 CFR 180):

Superfund Amendments and Reauthorization Act (SARA) Title III:

Hazard Categories Sections 311 / 312 (40 CFR 370.2):

Health Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

Physical None

Emergency Planning & Community Right to Know (40 CFR 355, App. A):

Extremely Hazardous Substance Section 302 - Threshold Planning Quantity:

SARA III Threshold Planning Quantity: None established

Reportable Quantity (49 CFR 172.101, Appendix):

CERCLA None established SARA III Reportable quantity: None established

Supplier Notification Requirements (40 CFR 372.45), 313 Reportable Components

SARA III De minimis concentration: There are no components of this product present

above de minimis concentrations.

Clean Air Act Toxic ARP Section 112r:

CAA 112R None established

Clean Air Act Socmi:

HON SOC None established

Clean Air Act VOC Section 111:

CAA 111 None established

Clean Air Act Haz. Air Pollutants Section 112: CAA None established

CAA 112I None established

CAA AP None established

State Right-to-Know Regulations Status of Ingredients

Pennsylvania:

CAS#	COMPONENT NAME
34590-94-8	Propanol, (2,methoxy-methylethoxy-)

PENN RTK

US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Wolmanized® L3 Outdoor® Wood

REVISION DATE: 04/10/2007 Page 9 of 10

PENN RTK 08 1989

PROPANOL, (2-METHOXYMETHYLETHOXY)-

New Jersey:

CAS#	COMPONENT NAME
60207-90-1	Propiconazole

NJ RTK

US. New Jersey Community Right-To-Know Survey, Table A: NJ Environmental Hazardous Substances [EHS] List (N.J. Admin. Code Title 7 Section 1G-2.1)

NJ RTK

2001

Substance no. 3442

PROPICONAZOLE (1-[2-(2,4-DICHLOROPHENYL)-4-PROPYL-1,3-DIOXOLAN-2-YL]-METHYL-1H-1,2,4-TRIAZOLE)

Massachusetts:

CAS#	COMPONENT NAME
34590-94-8	Propanol, (2,methoxy-methylethoxy-)

MASS RTK

US. Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

MASS RTK

04 1993

DIPROPYLENE GLYCOL METHYL ETHER

California Proposition 65:

CAS#	COMPONENT NAME

US CA CRT None established

US CA65CRT None established

WHMIS Hazard Classification:

16. OTHER INFORMATION

MSDS REVISION STATUS: Revised to meet the ANSI standard of 16 sections

Major References : Available upon request.

THIS MATERIAL SAFETY DATA SHEET (MSDS) HAS BEEN PREPARED IN COMPLIANCE WITH THE FEDERAL OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200. THE INFORMATION IN THIS MSDS SHOULD BE PROVIDED TO ALL WHO WILL USE, HANDLE, STORE, TRANSPORT, OR OTHERWISE BE EXPOSED TO THIS PRODUCT. THIS INFORMATION HAS BEEN PREPARED FOR THE GUIDANCE OF PLANT ENGINEERING, OPERATIONS AND MANAGEMENT AND FOR PERSONS WORKING WITH OR HANDLING THIS PRODUCT. THE MANUFACTERER BELIEVES THIS INFORMATION TO BE RELIABLE AND UP TO DATE AS OF THE DATE OF PUBLICATION BUT, MAKES NO WARRANTY THAT IT IS.

Wolmanized® L3 Outdoor® Wood

REVISION DATE: 04/10/2007 Page 10 of 10