Click anywhere in the top portion of this page for updated/expanded articles on oil storage tanks, inspection, testing, abandonment, removal, spill cleanup, leak reporting regulations, etc, online at InspectAPedia.com

7. REGULATIONS AND ADVISORIES

The international, national, and state regulations and guidelines regarding fuel oils in air, water, and other media are summarized in Table 7-1. There are only a few regulations that are specific to a particular fuel oil and these are indicated in the table.

An acute inhalation MRL of 0.02 mg/m³ was derived for fuel oil no. 2. The MRL is based on a LOAEL value of 65 mg/m³ for neurobehavioral effects (mild transient ataxia and CNS depression) in mice exposed to airborne concentrations of fuel oil no. 2.

An intermediate inhalation MRL of 0.01 mg/m³ was derived for fuel oil no. 1. The MRL is based on decreased blood glucose levels in male rats exposed to airborne concentrations of kerosene averaging 58 mg/m³ for 6 hours/day, 6 days/week for 14 weeks. Rats exposed to airborne concentrations of kerosene averaging 231 mg/m³ showed a decrease in blood glucose titers, as well as increased circulating levels of lactate and pyruvate.

The EPA has no oral reference dose (RfD) or inhalation reference concentration (RfC) for any of the fuel oils.

Under the Hazardous Materials Transportation Act, fuel oils are designated as hazardous substances subject to special requirements for packaging, labeling, and transportation (DOT 1989a, 1989b).

7. REGULATIONS AND ADVISORIES

TABLE 7-1. Regulations and Guidelines Applicable to Fuel Oils

Agency	Description	Information	References
INTERNATIONAL			
IARC	Carcinogenic classification		IARC 1989
	for occupational exposures		
	in petroleum refining	Group 2A ^a	
	Carcinogenic classification		
	marine diesel fuel	Group 2B ^b	
	residual (heavy) fuel oils	Group 2B	
	jet fuels	Group 3 ^c	
	distillate (light) diesel fuels	Group 3	
NATIONAL			
Regulations:			
a. Air:			
AFOSH	PEL TWA		Air Force 1989
	Petroleum distillates (naphtha)	400 ppm	
	STEL (15 minutes)		
	Petroleum distillates (naphtha)	500 ppm	
NIOSH	TWA		
	Petroleum distillates (naphtha)	85 ppm (350 mg/m ³)	NIOSH 1992
	Ceiling REL (15 minutes)	420 (1 000 4-3)	
	Petroleum distillates (naphtha) IDLH	438 ppm (1,800 mg/m ³)	
	Petroleum distillates (naphtha)	10 000	NIOCH 1000
OSHA	PEL TWA	10,000 ppm	NIOSH 1990 OSHA 1989a (29 CFR
OSHA	Petroleum distillates (naphtha)	400 ppm	1910.1000); OSHA
b. Other:			1989b
DOT	Hazardous Material Transportation Act:	Yes	DOT 1989a (49 CFR
201	Fuel oils are designated as	103	172.101
	hazardous materials which are subject		Appendix A); DOT
	to requirements for packaging, shipping,		1989b
	and transporting		
EPA	Toxic Substances Control Act: Manufacturers	Yes	EPA 1991a (40 CFR
	and processors of the C ₉ aromatic hydrocarbon		799.2175); EPA
	fraction must test this fraction for the		1987c
	following: neurotoxicity, mutagenicity,		
	developmental toxicity, reproductive effects,		
	and oncogenicity		
EPA	Marine Protection Research and Sanctuaries Act:	Yes	EPA 1991b (40 CFR
	Ocean dumping of organohalogen compounds or		227.6)
	oils of any kind which are known or		
	suspected carcinogens, mutagens, or teratogens		
	is prohibited except when they are present as trace contaminants		
	trace containmants		
Guidelines:			
a. Other:	-		
EPA	Domestic water supply must be virtually	Yes	EPA 1986c
	free from oil and grease, particularly		
	from the tastes and odors that emanate		
	from petroleum products		
	For aquatic life, levels must be ≤ 0.01 of	V	EDA 1007
	the lowest continuous flow 96-h LC ₅₀	Yes	EPA 1986c

Click anywhere in the top portion of this page for updated/expanded articles on oil storage tanks, inspection, testing, abandonment, removal, spill cleanup, leak reporting regulations, etc, online at InspectAPedia.com

7. REGULATIONS AND ADVISORIES

TABLE 7-1. Regulations and Guidelines Applicable to Fuel Oils (continued)

Agency	Description	Information	References
NATIONAL (Cont.)			
	Clean Water Act: Oil and grease are designated as conventional pollutants. Effluent limitations for oil and grease (polynuclear aromatic hydrocarbons) exist for almost all point sources under the general pretreatment standards for new and existing sources	Yes	EPA 1988b (40 CFR 403.2); EPA 1988c
	Pesticide subject to registration and/or reregistration (kerosene)	Yes	EPA 1989c (40 CFR 152.146); EPA 1989b
<u>STATE</u>			
Regulations and Guidelines: a. Air:			
a. Air:	Acceptable ambient air concentrations		NATICH 1991
Connecticut	(Navy Fuels JP-5)	2.00-1033	
Maryland	(8 hour)	2.00x10 ³ μg/m ³ 0.00	
Oklahoma	(24 hour)	1.00x10 ⁴ μg/m ³	
Texas Texas	(30 minutes) (annual)	$1.00 \times 10^3 \text{ µg/m}^3$ $1.00 \times 10^2 \text{ µg/m}^3$	
	Regulations on hydrocarbon emissions (kerosene, petroleum distillates, diesel, fuel oil)	Yes	CELDS 1991
Connecticut Kansas Wisconsin	,,		
	Regulations on volatile organic	Yes	CELDS 1991
Alabama	carbon emissions (VOC)		
Arizona Florida Maine			
Maryland Michigan New Jersey			
South Carolina Virginia Texas Washington, DC			
Maine Maine	Regulations on the open burning	Yes	CELDS 1991
Texas	of fuel oils (kerosene) Regulations for gas processing	Yes	CELDS 1991
	plants		
o. Water: Alaska	Aquatia life aritarian for tatal	15//	0
Alaska	Aquatic life criterion for total hydrocarbons in marine and surface waters	15 μg/L	State of Alaska 1989
	Aquatic life criterion for aromatic hydrocarbons in marine and surface waters	10 μg/L	State of Alaska 1989

Click anywhere in the top portion of this page for updated/expanded articles on oil storage tanks, inspection, testing, abandonment, removal, spill cleanup, leak reporting regulations, etc, online at InspectAPedia.com

7. REGULATIONS AND ADVISORIES

TABLE 7-1. Regulations and Guidelines Applicable to Fuel Oils (continued)

Agency	Description	Information	References
STATE (Cont.)			
Arkansas	Average or maximum allowable quantity of oil or grease discharged into surface waters	10 mg/L (average) 15 mg/L (maximum)	State of Arkansas 1991
Florida	Average or maximum allowable quantity of oil or grease discharged Class V waters (navigation, industrial use)	10 mg/L	State of Florida 1992
	Average or maximum allowable quantity of oil or grease discharged into all other surface waters	5 mg/L	State of Florida 1992
Maine	Drinking water quality guidelines and standards (fuel oil no. 2)	100 μg/L	FSTRAC 1988
Massachusetts	Maximum discharge concentration of oil or grease of petroleum origin in surface waters	15 mg/L	Commonwealth of Massachusetts 1988
Nebraska	Maximum petroleum oil concentration in surface waters	10 mg/L	State of Nebraska 1991
New York	Maximum contaminant level of kerosone in drinking water	50 μg/mL	State of New York 1989
South Dakota	Water quality standard for all petroleum products in surface waters	10 mg/L	State of South Dakota 1989
Virginia	Water quality standard for petroleum hydrocarbons in ground water	1 mg/L	Commonwealth of Virginia 1988
Wyoming	Water quality standard for all surface waters classes	10 mg/L	State of Wyoming 1990
c. Other:	Regulations on the transport of flammable/hazardous liquids (petroleum distillates or VOC)	Yes	CELDS 1991
Colorado Maryland Massachusetts Wisconsin			
Maine	Regulations on the disposal of special wastes including diesel fuels	Yes	CELDS 1991
California	Regulations on leaking underground fuel tanks	Yes	CELDS 1991
Wyoming	Regulations on well drilling for oil	Yes	CELDS 1991
Rhode Island	Regulations on oil pollution	Yes	CELDS 1991

^aGroup 2A = Probably carcinogenic to humans. This classification is not specified for the fuel oils discussed in this profile, nor for exposure to fuel oils by the general population; rather, this classification applies only to occupational exposures in petroleum refining.

AFOSH = Air Force Office of Health and Safety; CELDS = Computer-Environmental Legislative Data System; DOT = Department of Transportation; EPA = Environmental Protection Agency; IARC = International Agency for Research on Cancer; IDLH = Immediately Dangerous to Life or Health; NATICH = National Air Toxics Information Clearinghouse; NIOSH = National Institute for Occupational Safety and Health; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit; REL = Recommended Exposure Limit; STEL = Short Term Exposure Limit; TWA = Time-Weighted Average; VOC = Volatile Organic Compounds

Click anywhere in the top portion of this page for updated/expanded articles on oil storage tanks, inspection, testing, abandonment, removal, spill cleanup, leak reporting regulations, etc, online at InspectAPedia.com

^bGroup 2B = Possibly carcinogenic to humans

^cGroup 3 = Not classifiable as to its carcinogenicity to humans