

## HTV SELF-REGULATING HEATING CABLE



nVent RAYCHEM HTV self-regulating heating cable is designed for freeze protection or process temperature maintenance of pipes and vessels up to 205°C continuously, with a maximum exposure temperature of 260°C. The HTV cable has a solid construction with a high power retention (HPR) heating core and pressure extruded electrical insulation. It is then integrated with a robust metallic braid and a chemically resistant fluoropolymer outer jacket.

### FEATURES & BENEFITS

High power retention (HPR) heating core

Power retention: At least 95% after 10 years

Design life: 30 years or more depending on application

Simplified design in hazardous area: T3 and T2

Longer circuit lengths due to larger cross section conductors

Fast installation: cut-to-length, multiple overlaps allowed, meter markings, user-friendly connections kits

Safe and efficient in operation: no overheating, uniform pipe temperatures, energy saving technology

Reliable during long life: 10 year product warranty available, maintenance free

### SPECIFICATIONS

**Supply Voltage** 90 – 130 V

**Area Classification** Non-Hazardous; Hazardous

**Outer Jacket Material** High Temperature Fluoropolymer

**Ground Path Type** Braid

**Max Maintain or Continuous Exposure Temperature, Power On** 400 °F

**Max Intermittent Exposure Temperature, Power On/Off** 500 °F

**Max Cumulative Hours for Intermittent Exposure** 2000 h

Table 1/1

Catalog Number	Item Name	Nominal Power Output @ 50°F, 120V
P000004315	10HTV1-CT	10 W/ft
P000004316	12HTV1-CT	12 W/ft
P000004317	15HTV1-CT	15 W/ft
P000004318	20HTV1-CT	20 W/ft
P000004312	3HTV1-CT	3 W/ft
P000004313	5HTV1-CT	5 W/ft
P000004314	8HTV1-CT	8 W/ft

**Supply Voltage** 190 – 277 V

**Area Classification** Non-Hazardous; Hazardous

**Outer Jacket Material** High Temperature Fluoropolymer

**Ground Path Type** Braid

**Max Maintain or Continuous Exposure Temperature, Power On** 400 °F

**Max Intermittent Exposure Temperature, Power On/Off** 500 °F

**Max Cumulative Hours for Intermittent Exposure** 2000 h

Table 1/1

Catalog Number	Item Name	Nominal Power Output @ 50°F, 240V
P000004322	10HTV2-CT	10 W/ft
P000004323	12HTV2-CT	12 W/ft
P000004324	15HTV2-CT	15 W/ft
P000004325	20HTV2-CT	20 W/ft
P000004319	3HTV2-CT	3 W/ft
P000004320	5HTV2-CT	5 W/ft
P000004321	8HTV2-CT	8 W/ft

**North America**

Tel +1.800.545.6258  
Fax +1.800.527.5703  
thermal.info@nvent.com

**Europe, Middle East, Africa**

Tel +32.16.213.511  
Fax +32.16.213.604  
thermal.info@nvent.com

**Asia Pacific**

Tel +86.21.2412.1688  
Fax +86.21.5426.3167  
cn.thermal.info@nvent.com

**Latin America**

Tel +1.713.868.4800  
Fax +1.713.868.2333  
thermal.info@nvent.com



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

©2020 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.  
nVent reserves the right to change specifications without notice.