STM JOURNALS

Journal of Instrumentation Technology & Innovations
ISSN: 2249-4731 (Online), ISSN: 2347-7261 (Print)
Volume 9, Issue 3
www.stmjournals.com

Review on Electrical Wiring (Types, Sizes and Installation)

Mustafa T. Mohammed Alhashimi[1] , Yousif Jawad Kadhim Nukhailawi[2] , Ahmed Tahseen Ali[3]
[1]Al-Najaf Engineering Technical College, Alfurat Al-awsat Technical University.
[2]Al-Najaf Engineering Technical College, Alfurat Al-awsat Technical University.
[3]Al-Najaf Engineering Technical College, Alfurat Al-awsat Technical University.

ABSTRACT

Various influences that will affect our choice of electrical wiring involve color, label data with applications. The data-printed on the wire shell is totally that you requisite to select the right wire for the home. More often than not, the name(wire or cable) are applied to designate the similar thing, while they are essentially quite altered. Wire acts a single electrical conductor, whereas a cable is a group of wires swathed in sheathing. The term cable eventually denoted to a nautical line of numerous ropes applied to anchor ships, besides to an electrical context, cables (similar to wires) are applied to transmit electrical currents. Cables for manufacturing, commercial besides apartment buildings may involve numerous insulated conductors in an general jacket, with helical tape steel or aluminum armor , or else steel wire armor, besides perhaps as well an global PVC or lead jacket to protection from moisture and physical damage. Cables intended for very flexible service or in marine requests can be protected via woven bronze wires. Power or power supply cables (like ,computer networking) which are routed in or via air-handling spaces (plenums) of office buildings are requisite under the typical building code to be either covered in metal conduit, or evaluated to low flame and smoke manufacture.

Keywords: *nautical, Power, spaces, plenums, armour, ships, network, flex.*
Author for correspondence E-mail: inj. Must.@atu.edu.iq

INTRODUCTION

Electrical wiring is an electrical system of cabling and linked devices like switches, distribution boards, plugs, and light equipment in a building. Wiring is subject to protection standards to strategy with installation. Allowable wire and cable types and sizes are specified according to the circuit operating voltage and electric current capability, with further restrictions on the environmental conditions, such as ambient temperature range, moisture levels, and exposure to sunlight and chemicals. Associated circuit protection, control and distribution devices within a building's wiring system are subject to voltage, current and functional specification. Wiring protection codes vary via locality[1-3], state or region. The International Electro-technical Commission (IEC) is "struggling to harmonise wiring standards between member countries, while significant differences in design and installation necessities still exist. An electrical cable is a rally of one or more wires running side by side or bundled, which is applied to transfer electric current.

A cable rally is the composition of one or additional electrical cables and their corresponding connectors.[1] A cable rally is not necessarily suitable for connecting two devices but can be a partial product (e.g. to be soldered onto a printed circuit board with a connector mounted to the building). Cable assemblies can besides take the system of a cable tree or cable harness", applied to connect numerous terminals together[4-6].

Types of Electrical Wires: There are essentially 5 types of electrical wires[7-10]:

A. Triplex Electrical Wires: Triplex electrical wires are commonly applied in single-phase service drop conductors, among the power pole besides weather heads. They are composed of two insulated aluminum wires wrapped with a third bare wire that is applied as a public neutral. The neutral is commonly of a smaller gauge besides grounded at each the electric meter plus the transformer


© STM Journals 2019. All Rights Reserved

B. Main Feeder Electrical Wires : Central power feeder wires act the wires that associate the service weather head to the house. They're made through stranded or solid THHN wire besides the cable installed act 30% further than the load essential.

C. Panel Feed Electrical Wires : Panel feed cables are normally black insulated THHN wire. These are applied to power the core junction container and the circuit breaker panels. Just like core power feeder electrical wires, the cables must be rated to 50% more than the actual load.

D. Non-Metallic Sheathed Electrical Wires : Non-metallic sheath electrical-wire, or Romex, is applied in most building besides has (2 to 3) conductors, every with plastic insulation, besides a bare crushed wire. The separated wires are protected through another coating of non-metallic sheathing. Since it's moderately cheaper and available in ratings to (10 to 20 amps), this type is favorite in-house wiring.

E. Single Strand Electrical Wires : Single strand wire besides applications THHN wire, though there are other variants. Every wire is separate with numerous wires can be drawn together through a pipe certainly. Single strand electrical-wires are the most common choice for layouts[10-14] which use pipes to involve wires., figure (1).



Fig(1): *Coding of Wires Via Colors*

Classification of Electrical-Cables : There are other 10 different forms of cables available currently, designed to applications about from transmission to heavy industrial application. Selected of the most normally-used ones involve[15-20]:

A. Non-Metallic (Sheathed-Cable) : These cables are also known as non-metallic building wire or NM cables. They feature a flexible plastic jacket with two to four wires (TECK cables are roofed with thermoplastic insulation) besides a bare wire to grounding. Special varieties of this cable are applied to underground or outdoor use, while NM-B plus NM-C non-metallic sheathed cables are the most common form of indoor residential cabling.

B. Underground (Feeder-Cable) : These cables are quite similar to NM cables, but instead of every electrical-wire being individually wrapped in thermoplastic, wires are collected together then embedded in the bendable material. Available in a multiplicity of gauge sizes, UF cables are often applied to outdoor lighting and in-pounded uses and applications. Their high water-resistance makes them ideal to damp areas like gardens as well as open-to-air lamps, pumps, etc.

C. Metallic Sheathed Cable : Also known as armored or BX cables, metal-sheathed cables are often used to supply mains electricity or for large appliances. They feature three plain stranded copper wires (one wire for the current, one grounding wire and one neutral wire) that are insulated with cross-linked polyethylene, PVC bedding and a black PVC sheathing. BX cables with steel wire sheathing are often used for outdoor applications and high-stress installations.

D. Multi-Conductor Cable : This is a cable kind that is commonly applied in homes, since it is simple to use and well-insulated. Multi-conductor or multi-core (MC) cables feature more than one conductor, every of which is insulated individually. besides, an outer insulation layer is added to extra security. Different varieties are used in

industries, like the audio multicore 'snake cable' used in the music industry.

E. Coaxial Cable : A coaxial (occasionally heliax) cable features a tubular insulating coating that shields an inner conductor that is further bounded via a tubular conducting shield, and might besides feature an outer sheath for extra insulation. Called 'coaxial' since the two inner shields share the same geometric axis, these cables are normally applied to carrying television signals with joining video equipment.

F. Unshielded Twisted Pair Cable : Like the name suggests, this type consists of two wires that are twisted together. The individual wires are not insulated, which makes this cable perfect for signal transmission and video applications. Since they are more affordable than coaxial or optical fiber cables, UTP cables are often used in telephones, security cameras and data networks. For indoor use, UTP cables with copper wires or solid copper cores are a popular choice, since they are flexible and can be easily bent for in-wall installation.

G. Ribbon Cable: Ribbon cables are often applied in computers plus peripherals, with various conducting wires that run parallel to each other on a flat plane, leading to a visual resemblance to flat ribbons. These cables are quite flexible with can merely handle low voltage uses and applications.


H. Direct-Buried Cable : Besides known as DBCs, these cables are especially-premeditated coaxial or bundled fiber-optic cables, that do not need any added sheathing, insulation or piping before being buried underground. They feature a heavy metal core with numerous layers of banded metal sheathing, heavy rubber shells, shock-absorbing gel and waterproof wrapped thread-fortified tape. High tolerance to temperature variations, moisture besides other environmental elements makes them a general choice for transmission or communication necessities.

I. Twin (Lead-Cable): These are flat two-wire cables which are applied to transmission among an antenna and receiver, similar to TV blues radio.

J. Twinaxial Cable : This is a different of coaxial cables, which features two inner conductors instead of one besides is applied to very-short-range high-speed signals.

K. Paired Cable : With double individually insulated conductors, that cable is typically applied in (DC or low-frequency AC)- uses and applications.

L. Twisted Pair : This cable is analogous to paired cables, while the inner insulated wires are twisted or intertwined[20-29]., figure (2).



Fig(2): Parts of Cable

Resources for wiring interior electrical systems in constructions vary depending on:

A. Intended application besides amount of power demand on the circuit


B. Class of occupancy besides size of the construction

C. National besides local rules

D. Environment in which the electrical-wiring need activate.

In a light profitable environment, more regular wiring variations can be estimated, large tools may be fixed and special conditions of

temperature or moisture may apply. Heavy industries have more demanding wiring requirements, like very large currents besides higher voltages, frequent changes of equipment layout, corrosive, or wet or explosive atmospheres. In facilities that handle flammable gases or liquids, special rules may govern the installation besides wiring of electrical equipment in hazardous areas. Wires with cables are rated via the circuit voltage, heat rating and environmental conditions (moisture, sunlight, oil, chemicals) in which they can be applied[30-39]. A wire or cable has a voltage (to neutral) rating and a maximum conductor surface temperature rating. The amount of current a cable or wire can safely carry depends on the installation conditions[40-49]., types of wires in figure(3).




Fig(3): Types of Electrical Wires

Modern Wiring Materials:

Modern non-metallic sheathed cables, like (US with Canadian) kinds NMB besides NMC, involve two to four wires covered with thermoplastic insulation, plus a bare wire for grounding (bonding), bounded via a flexible plastic jacket. Certain versions wrap the individual conductors in paper before the plastic jacket is applied. Special versions of non-metallic sheathed cables, such as US Type UF, are designed to direct underground burial (often with separate mechanical shield) or exterior use where exposure to ultraviolet radiation (UV) is a possibility. These cables differ in having a moisture-resistant construction, lacking paper or other absorbent fillers, and being formulated for UV resistance[50-59]. Rubber-like synthetic polymer insulation is used in industrial cables and power cables installed underground because of its superior moisture resistance. Insulated cables are rated via their allowable operating voltage and their maximum operating temperature at the conductor surface. A cable may carry multiple usage ratings for applications, for example, one rating for dry installations and another when exposed to moisture or oil.

Normally, single conductor building wire in small sizes is solid wire, since the wiring is not requisite to be very flexible. Building wire conductors larger than 10 AWG (or about 6 mm^2) are stranded for flexibility through installation, while are not sufficiently pliable to use as appliance cord. Cables for industrial, commercial and apartment buildings may "involve numerous insulated conductors in an overall jacket, with helical tape steel or aluminum armour, or steel wire armour, and perhaps as well an overall PVC or lead jacket for protection from moisture and physical damage. Cables intended for very flexible service or in marine applications may be sheltered via woven bronze wires. Power or communications cables (like computer networking) that are routed in or via air-handling spaces (plenums) of office buildings are requisite under the model building code to be either encased in metal conduit, or rated for low flame and smoke production. Electrical cables are used to connect two or more devices, enabling the transfer of electrical signals or power from one device to the other. Cables are used for a wide range of purposes, and each must be tailored for that purpose. Cables are used extensively in electronic devices for power and signal circuits. Long-distance communication takes place over undersea cables. Power cables are used for bulk transmission of alternating and direct current power, especially using high-voltage cable. Electrical cables are extensively used in building wiring for lighting, power and control circuits

permanently installed in buildings. Since all the circuit conductors required can be installed in a cable at one time, installation labor is saved compared to certain other wiring methods. Physically, an electrical cable is an assembly consisting of one or more conductors with their own insulations and optional screens, individual covering(s), assembly protection and protective covering(s). Electrical cables may be prepared more flexible via stranding the wires. In this process, smaller individual wires are twisted or braided together to produce larger wires that are more flexible than solid wires of similar size. Bunching small wires before concentric stranding adds the most flexibility. Copper wires in a cable may be bare, or they may be plated with a thin layer of another metal, most often tin but sometimes gold, silver or some other material. Tin, gold, and silver are much less prone to oxidation than copper, which may lengthen wire life, and makes soldering easier. Tinning is also used to provide lubrication between strands. Tinning was used to help removal of rubber insulation. Tight lays during stranding makes the cable extensible (CBA – as in telephone handset cords). Cables can be securely fastened and organized, such as by using trunking, cable trays, cable ties or cable lacing. Continuous-flex or flexible cables used in moving applications within cable carriers can be secured using strain relief devices or cable ties. At high frequencies, current tends to run along" the surface of the conductor[60-69]. This is known as the skin effect., figure(4)



Fig(4): Coaxial cable

These effects are often undesirable, in the first case amounting to unwanted transmission of energy which may adversely affect nearby equipment or other parts of the same piece of equipment; besides in the second case, unwanted pickup of noise that may mask the desired signal being carried via the cable, or, if the cable is carrying power supply or control voltages, pollute them to like an extent as to cause equipment malfunction. The first solution to these problems is to keep cable lengths in buildings short since pick up and transmission are essentially proportional to the length of the cable. The second solution is to route cables away from trouble. Beyond this, there are particular cable designs that minimize electromagnetic pickup and transmission. Three of the principal design systems are shielding, coaxial geometry, and twisted-pair geometry.

Shielding makes applications of the electrical principle of the Faraday cage. The cable is encased for its entire length in foil or wire mesh. All wires running inside this shielding layer will be to a large extent decoupled from external *electrical* fields, particularly if the shield is connected to a point of constant voltage, such as earth or ground. Simple shielding of this type is not greatly effective against low-frequency *magnetic* fields, however–like magnetic "hum" from a nearby power transformer. A beached shield on cables operating at 2.5 kV or more gathers leakage current and capacitive current, protecting people from electric shock and equalizing stress on the cable insulation.

Coaxial design assistances to "further reduce low-frequency magnetic transmission besides pickup. In this design the foil or mesh shield has a circular cross section besides the inner

conductor is exactly at its center. This sources the voltages involved via a magnetic field between the shield with the core conductor to consist of two nearly equal magnitudes which cancel every other. A twisted pair has two wires of a cable twisted around each other. This can be demonstrated by putting one end of a pair of wires in a hand drill and turning while maintaining moderate tension on the line. Where the interfering signal has a wavelength that is long compared to the pitch of the twisted pair, alternate lengths of wires develop opposing voltages, tending to cancel the effect" of the interference[70-79].

Sizes of Stranded Wire AWG

AWG gauges are similarly applied to "designate stranded wire. In this event, it describes a wire that is equal in cross-sectional area to the total of all the cross-sectional areas of the individual strands; the gaps between strands are not counted. When made with circular strands, these gaps occupy about 10% of the wire area, thus requiring a wire about 5% thicker than equivalent solid wire[80]. Stranded wires are specified with three numbers, the overall AWG size, the number of strands, and the AWG size of a strand. The numeral of strands and the AWG of a strand are separated by a slash. For example, a 22 AWG 7/30 stranded wire is a 22 AWG wire made" from seven strands[80-88] of 30 AWG wire., figure(5)




Fig.(5): *Standard Wires*

CONCLUSIONS

Cables commonly are protected with special fittings wherever they enter electrical apparatus; this may be a simple screw clamp to jacketed cables in a dry position, or a polymer-gasketed cable connector that automatically engages the amour of an armored cable and supplies a water-resistant connection. Special cable fittings may be applied to prevent explosive gases from flowing in the interior of jacketed cables, where the cable passes through areas where flammable gases are current. To avoid loosening of the associates of individual conductors of a cable, cables must be maintained near their entrance to devices and at systematic intervals along their runs. In tall buildings, special designs are requisite to provision the conductors of vertical runs of cable. Commonly, merely one cable per fitting is permitted, unless the fitting is rated or summarized for multiple cables. They must also resist corrosion caused by salt water or salt spray, which is accomplished through the use of thicker, specially constructed jackets, and via tinning the individual wire stands.

REFERENCES

[1] Popova A, Christov M, Vasilev A. 2015. Mono- and dicationic benzothiazolic quaternary ammonium bromides as mild steel corrosion inhibitors. Part III: influence of the temperature on the inhibition process," Corrosion Science, 94,. 70–78p.

[2] Sturgeon, W., 1825, Improved Electro Magnetic Apparatus, *Trans. Royal Society of Arts, Manufactures, & Commerce* (London) 43: pp. 37–52, as cited in Miller, T.J.E, 2001, Electronic Control of Switched Reluctance Machines, *Newnes*, p. 7. ISBN 0-7506-5073-7

[3] Windelspecht, Michael, 2003, Groundbreaking Scientific Experiments, Inventions, and Discoveries of the 19th Century, XXII, Greenwood Publishing Group, ISBN 0-313-31969-3

[4] Pops, Horace, 2008, Processing of wire from antiquity to the future, Wire Journal International, June, pp 58-66.

[5] Pops, Horace, 1995, Physical Metallurgy of Electrical Conductors, in Nonferrous Wire Handbook, Volume 3: Principles and Practice, The Wire Association International, pp. 7-22

[6] Weast, Robert C. & Shelby, Samuel M. Handbook of Chemistry and Physics, 48th edition, Ohio: The Chemical Rubber Co. 1967–1968: F-132

[7] *W.F. Gale; T.C. Totemeir, eds. (2004), Smithells Metals Reference Book (8th ed.), Elsevier Butterworth Heinemann Co. and ASM International , ISBN 0-7506-7509-8*

[8] Rich, Jack C., 1988, The Materials and Methods of Sculpture. Courier Dover Publications. p. 129. ISBN 0-486-25742-8, https://books.google.com/?id=hW13qhOFa7gC

[9] *Mustafa T. Mohammed Alhashimi, Ruaa Shallal Abbas Anooz , Ali Sabah Noori .* Review on Generation sources of Electrical Power. *Journal of Instru Techno & Innovs*. 2019; 9(3): 8–16p..

[10] Pops, Horace; Importance of the conductor and control of its properties for magnet wire applications, in Nonferrous Wire Handbook, Volume 3: Principles and Practice, The Wire Association International, pp 37-52.

[11] Terrell Croft and Wilford Summers (ed), *American Electrican's Handbook, Eleventh Edition*, McGraw Hill, New York (1987) ISBN 0-07-013932-6 page 9-86

[12] R. M. Black *The History of Electric Wires and Cables*, Peter Pergrinus, London 1983 ISBN 0-86341-001-4.

[13] *Swiger Coil Systems. "Edgewound Coils". Swiger Coil Systems, A Wabtec Company. Archived from the original on 19 December 2010. Retrieved 1 January 2011.*

[14] Mustafa T. Mohammed Alhashimi, Nawfel Muhammed Baqer Muhsin., 2019. Treatment of (Electric Wires and Machines)-Erosion via Engineering Materials by the Coating., NeuroQuantology , November 2019 ,17 ,11 , Page 11-16 ., 10.14704/nq.2019. 17.11.NQ19108.

[15] Jack Ogden, 'Classical Gold wire: Some Aspects of its Manufacture and Use', *Jewellery Studies*, 5, 1991, pp. 95–105.

[16] Jack Ogden, 'Connections between Islam, Europe, and the Far East in the Medieval Period: The Evidence of the Jewelry Technology'. Eds P. Jett, J Douglas, B. McCarthy, J Winter. *Scientific Research in the Field of Asian Art. Fiftieth-Anniversary Symposium Proceedings*. Archetype Publications, London in association with the Freer Gallery of Art, Smithsonian Institution, 2003.

[17] H. R. Schubert, 'The wiredrawers of Bristol' *Journal Iron & Steel Institute* 159 (1948), 16-22.

[18] M. B. Donald, *Elizabethan Monopolies: Company of Mineral and Battery Works* (Olver & Boyd, Edinburgh 1961), 95-141.

[19] D. G. Tucker, 'The seventeenth century wireworks at Whitebrook, Monmouthshire ' *Bull. Hist. Metall. Gp* 7(1) (1973), 28-35.

[20] Nawfel Muhammed Baqer Muhsin ,Hayder H K, Noor H. D ,Nagham M A. 2019. "Preparation of Chemical Inhibitors to Treat the Corrosion and Erosion of Machines".,International Journal of Engineering, Applied and Management Sciences Paradigms., 54 , 3, 89-93p.

[21] Nawfel Muhammed Baqer Muhsin, Noorhan Ali H, Nagham M A ,.2019, Review on Corrosion and Rust Inhibition of Machines in Chemical Engineering Field. International Journal of Thermodynamics and Chemical Kinetics.; 5 (1) 1–10 p ., www.journalspub.com

[22] Ali M H., Azwan B S., Qahtan A A., Mohammed S A., Nawfel Muhammed Baqer Muhsin., Bassam A S. 2019. Thermal Performance of Corrugated Solar Air Heater Integrated with Nanoparticles to Enhanced the Phase Change Material (PCM) .,International Journal of Mechanical & Mechatronics Engineering IJMME-IJENS Vol:19 No:05, 1-17.

[23] *Hogsett, Jamie; Oehler, Sara (2012). Show Your Colors: 30 Flexible Beading Wire Jewelry Projects. Kalmbach Books. p. 12. ISBN 978-0-87116-755-2.*

[24]*Croft, Terrell; Summers, Wilford, eds. (1987). American Electricans' Handbook (11 ed.). New York: McGraw Hill. ISBN 0-07-013932-6.*

[25] *Schneider, Norman Hugh (1916). "2-4". Wiring houses for the electric light; together with special references to low voltage battery systems. New York: Spon and Chamberlain.*

[26] *Knox, Charles E. (1909). Electric Wiring Instruction Paper. Chicago: American School of Correspondence.*

[27] *Krasner, Steve. "Knob-and-Tube Wiring: What's the Big Deal?". Only Connect: Electrical FAQ's. Retrieved 2011-03-19.*

[28] *Nick Gromicko, Rob London and Kenton Shepard. "Knob-and-Tube Wiring" . Inspecting the World. Retrieved 2011-03-19.*

[29] *Carson Dunlop. "Knob and Tube Wiring & Home Owners' Insurance" . Carson Dunlop Report. Retrieved 2011-03-19.*

[30] *KNTelectric. "Knob and Tube Wiring - an unbiased review". Archived from the original on 2011-12-02.*

[31] *Friedman, Daniel. "Electrical Knob & Tube Electrical Wiring Inspection, Evaluation, & Repair Suggestions" . InspectAPedia. InspectAPedia.com. Retrieved 2011-03-19.*

[32] *William Kibbel III. "Ask the Home Inspector: Knob and Tube Wiring". Old House Web*. Retrieved 2010-04-13.

[33]*Jones, D.A. (1991), "Electrical engineering: the backbone of society", IEE Proceedings A - Science, Measurement and Technology , 138 (1): 1–10,* doi*:*10.1049/ip-a-3.1991.0001

[34]*Moller, Peter; Kramer, Bernd (December 1991), "Review: Electric Fish", BioScience, American Institute of Biological Sciences, 41 (11): 794–96 [794]* , doi*:*10.2307/1311732, JSTOR 1311732

[35]*Stewart, Joseph (2001), Intermediate Electromagnetic Theory, World Scientific, p. 50,* ISBN 981-02-4471-1

[36]*Simpson, Brian (2003), Electrical Stimulation and the Relief of Pain, Elsevier Health Sciences, pp. 6–7,* ISBN 0-444-51258-6

[37]*Diogenes Laertius. R.D. Hicks (ed.).* "Lives of Eminent Philosophers, Book 1 Chapter 1 [24]". *Perseus Digital Library. Tufts University*. Retrieved 5 February2017. *Aristotle and Hippias affirm that, arguing from the magnet and from amber, he attributed a soul or life even to inanimate objects.*

[38]*Aristotle. Daniel C. Stevenson (ed.).* "De Animus (On the Soul) Book 1 Part 2 (B4 verso)". *The Internet Classics Archive. Translated by J.A. Smith*. Retrieved 5 February 2017. *Thales, too, to judge from what is recorded about him, seems to have held soul to be a motive force, since he said that the magnet has a soul in it because it moves the iron.*

[39]*Frood, Arran (27 February 2003),* Riddle of 'Baghdad's batteries', *BBC*, retrieved 2008-02-16

[40]*Baigrie, Brian (2007), Electricity and Magnetism: A Historical Perspective, Greenwood Press, pp. 7–8,* ISBN 978-0-313-33358-3

[41]*Chalmers, Gordon (1937), "The Lodestone and the Understanding of Matter in Seventeenth Century England ", Philosophy of Science, 4 (1): 75–95* , doi*:*10.1086/286445

[42] *Guarnieri, M. (2014). "Electricity in the age of Enlightenment". IEEE Industrial Electronics Magazine. 8 (3): 60–63.* doi*:*10.1109/MIE.2014.2335431.

[43] *Srodes, James (2002),* Franklin: The Essential Founding Father*, Regnery Publishing, pp.* 92–94, ISBN 0-89526-163-4 *It is uncertain if Franklin personally carried out this experiment, but it is popularly attributed to him.*

[44]Uman, Martin *(1987),* All About Lightning (PDF), *Dover Publications,* ISBN 0-486-25237-X

[45] *Riskin, Jessica (1998),* Poor Richard's Leyden Jar: Electricity and economy in Franklinist France (PDF), *p. 327*

[46] *Guarnieri, M. (2014). "The Big Jump from the Legs of a Frog". IEEE Industrial Electronics Magazine. 8 (4): 59–61, 69.* doi*:*10.1109/MIE.2014.2361237.

[47] *Kirby, Richard S. (1990),* Engineering in History*, Courier Dover Publications, pp.* 331–33, ISBN 0-486-26412-2

[48] *Berkson, William (1974) Fields of force: the development of a world view from Faraday to Einstein p.148. Routledge , 1974*

[49]*Sears, Francis; et al. (1982) , University Physics, Sixth Edition, Addison Wesley,* ISBN 0-201-07199-1

[50]*Hertz, Heinrich (1887).* "Ueber den Einfluss des ultravioletten Lichtes auf die electrische Entladung". Annalen der Physik. *267 (8): S.*

983–1000 . Bibcode:1887An P...267.. 983H. doi:10.1002/andp.18872670827.

[51]*John Sydney Blakemore,* Solid state physics, *pp. 1–3, Cambridge University Press, 1985 ISBN 0-521-31391-0.*

[52]*Richard C. Jaeger, Travis N. Blalock* , Microelectronic circuit design, *pp. 46–47, McGraw-Hill Professional, 2003 ISBN 0-07-250503-6.*

[53]*Moskowitz, Sanford L. (2016).* Advanced Materials Innovation: Managing Global Technology in the 21st century. John Wiley & Sons. *p. 168* . ISBN 9780470508923.

[54] Feldman, Leonard C. *(2001).* "Introduction ". *Fundamental Aspects of Silicon Oxidation.* Springer Science & Business Media. *pp. 1–11* . ISBN 9783540416821.

[55]*Golio, Mike; Golio, Janet (2018).* RF and Microwave Passive and Active Technologies. CRC Press. *pp. 18–2.* ISBN 9781420006728.

[56]*Shirriff, Ken (30 August 2016).* "The Surprising Story of the First Micro processors". IEEE Spectrum. Institute of Electrical and Electronics Engineers. Retrieved 13 October 2019.

[57] *Duffin, W.J. (1980),* Electricity and Magnetism, 3rd edition, *McGraw-Hill* , ISBN 0-07-084111-X

[58]*Umashankar, Korada (1989) , Introduction to Engineering Electromagnetic Fields, World Scientific, pp. 77–79,* ISBN 9971-5-0921-0

[59]*Trefil, James (2003),* The Nature of Science: An A–Z Guide to the Laws and Principles Governing Our Universe, *Houghton Mifflin Books, p.* 74, ISBN 0-618-31938-7

[60]*Shectman, Jonathan (2003) , Groundbreaking Scientific Experiments, Inventions, and Discoveries of the 18th Century, Greenwood Press, pp. 87–91* , ISBN 0-313-32015-2

[61]*Sewell, Tyson (1902), The Elements of Electrical Engineering, Lockwood, p. 18. The* Q *originally stood for 'quantity of electricity', the term 'electricity' now more commonly expressed as 'charge'.*

[62] *Close, Frank (2007), The New Cosmic Onion: Quarks and the Nature of the Universe, CRC Press, p. 51,* ISBN 978-1-58488-798-0

[63] *Ward, Robert (1960), Introduction to Electrical Engineering, Prentice-Hall, p. 18*

[64]*Solymar, L. (1984),* Lectures on electromagnetic theory, *Oxford University Press, p.* 140, ISBN 0-19-856169-5

[65]*Berkson, William (1974),* Fields of Force: The Development of a World View from Faraday to Einstein, *Routledge, p.* 370, ISBN 0-7100-7626-6 *Accounts differ as to whether this was before, during, or after a lecture.*

[66] *Bird, John (2007), Electrical and Electronic Principles and Technology, 3rd edition, Newnes,* ISBN 9781417505432

[67]*Morely & Hughes, Principles of Electricity, Fifth edition, p. 73,* ISBN 0-582-42629-4

[68]*Naidu, M.S.; Kamataru, V. (1982), High Voltage Engineering, Tata McGraw-Hill, p. 2,* ISBN 0-07-451786-4

[69]*Naidu, M.S.; Kamataru, V. (1982), High Voltage Engineering, Tata McGraw-Hill, pp. 201–02,* ISBN 0-07-451786-4

[70] Paul J. Nahin *(9 October 2002). Oliver Heaviside: The Life, Work, and Times of an Electrical Genius of the Victorian Age. JHU Press.* ISBN 978-0-8018-6909-9.

[71] *Serway, Raymond A. (2006), Serway's College Physics, Thomson Brooks, p. 500* , ISBN 0-534-99724-4

[72]*Saeli, Sue; MacIsaac, Dan (2007),* "Using Gravitational Analogies To Introduce Elementary Electrical Field Theory Concepts", *The Physics Teacher , 45 (2): 104,* Bibcode:2007PhTea.45.104S, doi:10.1119/1.2432088, retrieved 2007-12-09

[73] *Thompson, Silvanus P. (2004), Michael Faraday: His Life and Work, Elibron Classics, p. 79,* ISBN 1-4212-7387-X

[74] *Nadia Izet Mahdi ,Nadia Ezzat Al-kirbasee. 2015. NATURAL BOND ORBITAL (NBO) POPULATION ANALYSIS OF OS3 (CO) 10{M-PH2PC (ME) 2PPH2}.,Journal of Research in Applied, Natural and Social Sciences.,1(2), 111-118.*

[75]*Alexander, Charles; Sadiku, Matthew (2006), Fundamentals of Electric Circuits (3, revised ed.), McGraw-Hill,* ISBN 9780073301150

[76]*Dell, Ronald; Rand, David (2001), "Understanding Batteries", NASA Sti/Recon Technical Report N, Royal Society of Chemistry, 86: 2–4* , Bibcode:1985STIN .8619754M , ISBN 0-85404-605-4

[77]*McLaren, Peter G. (1984), Elementary Electric Power and Machines, Ellis Horwood, pp. 182–83,* ISBN 0-85312-269-5

[78] *Patterson, Walter C. (1999) , Transforming Electricity: The Coming Generation of Change, Earthscan, pp. 44–48,* ISBN 1-85383-341-X

[79]*ReVelle, Charles and Penelope (1992)*, The Global Environment: Securing a Sustainable Future, *Jones & Bartlett, p.* 298, ISBN 0-86720-321-8

[80]*Danish Ministry of Environment and Energy*, "F.2 The Heat Supply Act ", *Denmark's Second National Communication on Climate Change, archived from* the original *on January 8, 2008*, retrieved 2007-12-09

[81] *Herrick, Dennis F. (2003), Media Management in the Age of Giants: Business Dynamics of Journalism, Blackwell Publishing*, ISBN 0-8138-1699-8

[82]*Tleis, Nasser (2008), Power System Modelling and Fault Analysis, Elsevier, pp. 552– 54*, ISBN 978-0-7506-8074-5

[83]*Grimnes, Sverre (2000), Bioimpedance and Bioelectricity Basic, Academic Press, pp. 301–09*, ISBN 0-12-303260-1

[84] *Lipschultz, J.H.; Hilt, M.L.J.H. (2002), Crime and Local Television News, Lawrence Erlbaum Associates, p. 95* , ISBN 0-8058-3620-9

[85] *Encrenaz, Thérèse (2004), The Solar System, Springer, p. 217*, ISBN 3-540-00241-3

[86]*Ivancevic, Vladimir & Tijana (2005), Natural Biodynamics, World Scientific, p. 602*, ISBN 981-256-534-5

[87] *Kandel, E.; Schwartz, J.; Jessell, T. (2000)*, Principles of Neural Science, *McGraw-Hill Professional, pp.* 27–28 , ISBN 0-8385-7701-6

[88] *Davidovits, Paul (2007), Physics in Biology and Medicine, Academic Press, pp. 204–05* , ISBN 978-0-12-369411-9

[89]*Jackson, Mark (4 November 2013)*, Theoretical physics – like sex, but with no need to experiment, *The Conversation*

[90]*Van Riper, A. Bowdoin (2002), Science in popular culture: a reference guide, Westport :* Greenwood Press, *p. 69*, ISBN 0-313-31822-0

Cite this Article : *Mustafa T. Mohammed Alhashimi , Yousif Jawad Kadhim Nukhailawi , Ahmed Tahseen Ali. Review* on Electrical Wiring (Types, Sizes, and Installation). *J. Instr. Techno & Innov.* 2019; 9(3):31–40 p.