

CLICK ANYWHERE on THIS PAGE to RETURN to GEOTEXTILES at [InspectAmedia.com](https://www.inspectapedia.com)

Non-Woven Geotextile Fabric - EGLS3

Series: Non-Woven Geotextile Fabric

Recommended Applications: Drainage, Filtration

EGLS3 meets or exceeds the values listed below:

| Fabric Property | Test Method | Units | Minimum Average Roll Value |
|------------------|-------------|---------------------|----------------------------|
| Weight (Typical) | ASTM D 5261 | oz/sy | >3.0 |
| Grab Tensile | ASTM D 4632 | lbs. | 62 |
| Grab Elongation | ASTM D 4632 | % | >55 |
| Trap Tear | ASTM D 4533 | lbs. | 24 |
| CBR Puncture | ASTM D 6241 | lbs. | 179 |
| Water Flow | ASTM D 4491 | gpm/ft ² | 88 |
| UV Resistance | ASTM D 4355 | % | 70 |
| AOS | ASTM D 4751 | US Sieve | #70 |

Values provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.

To the best of our knowledge, the information contained herein is accurate. However, Eastgate Supply cannot anticipate all conditions under which the above product information and the products which we distribute or the products of other distributors or manufacturers in combination with the products which we offer, may be used. We accept no responsibility for results obtained by the application of this information or the safety or suitability of the products we distribute either alone or in combination with other products. Final determination of the suitability of any information or material for the used contemplated, or its manner of use, and whether the suggested use infringes any patents is the sole responsibility of the user.

Please note: Eastgate Supply is a distributor of geotextile fabric, not the manufacturer. We source material from a number of different United States based geotextile manufacturers.