

MATERIAL SAFETY DATA SHEET

Acculam™ Melaglas



Accurate Plastics, Inc.
18 Morris Place
Yonkers, New York 10705-1929
Phone (914) 476-0700
FAX (914) 476-0527
www.accum.com

Section 1. Chemical Product and Company Identification

<i>Product name</i> Acculam™ Melaglas	<i>Trade Name</i> NEMA Grades G5/G9
<i>Manufacturer</i> Accurate Plastics, Inc. 18 Morris Place Yonkers, NY 10705-1929	<i>IN CASE OF EMERGENCY:</i> Tel: 914-476-0700 Chemtrec:
<i>Date of Preparation:</i> 11/29/07	Replaces: 10/20/04
<i>Preparers Name</i> KJ Soltys	

Section 2. Composition, Information on Ingredients

<i>Component Information</i>		<i>Exposure Limits</i>	
<i>Chemical Name</i>	<i>CAS #</i>	<i>TLV, TWA ACGIH</i>	<i>OSHA PEL, TWA</i>
Fiberglass Continuous Filament	65997-17-3	10 mg/m ³ (dust)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable)
Melamine/formaldehyde Resin	N/L	N/A	N/A

Dust generated during grinding, cutting, or drilling fiber glass reinforced plastic produces respirable fiber shaped plastic (organic) particles which has an OSHA PEL of 5 mg/m³ and nonrespirable fibrous glass dust regulated by OSHA as noted above. Trace amounts (<0.05%) of formaldehyde may be present as an unreacted polymer precursor which may be released during machining operations as a co-contaminant with the dust. Formaldehyde has an OSHA PEL of 0.75 ppm.

N/A = Not Applicable N/L = Not Listed

Section 3. Hazards Identification

Dust generated during machining and grinding operations may cause skin and/or eye irritation. Fumes from thermal decomposition or burning may irritate eyes, nose, and throat. Minimize operator exposure to dust and fumes.	
Routes of Exposure	Symptoms
Inhalation	Inhalation of dust during machining and grinding operations may cause moderate irritation to mucous membranes and coughing.
Skin	Contact with dust may cause moderate skin irritation.
Eyes	Contact with dust may cause moderate eye irritation, itching and redness.
Ingestion	Not determined
Cancer	OSHA: N/A IARC: N/A NTP: N/A There are trace quantities of formaldehyde contained in the resin matrix. Formaldehyde is a Human Carcinogen according to IARC and classified as Reasonably Anticipated To Be a Human Carcinogen by NTP.
Chronic	Dust generated during grinding, cutting, or drilling fiber glass reinforced plastic contains respirable fiber shaped plastic (organic) particles and nonrespirable fibrous glass dust. Prolonged inhalation of dust can produce lung disease.

Section 4. First Aid Measures

Eyes	Immediately wash the eyes with large amounts of water for at least 15 minutes, occasionally lifting the lower and upper lids. Get medical attention immediately. Contact lenses should not be worn when working with this material.
Skin	Immediately wash the contaminated skin with soap and water. If redness, itching or a burning sensation develops, get medical attention.
Inhalation	Immediately move the exposed person to fresh air. If not breathing, give artificial respiration and get immediate medical attention.
Ingestion	If large quantities have been swallowed, DO NOT INDUCE VOMITING. If victim is conscious and alert, give 2 - 4 cups of lukewarm water. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flash Point	N/D
Flammability Classification OSHA/NFPA	Flash Pt. <00°F Class: Solid
Extinguishing Media	Carbon dioxide, water, foam.
Unusual Fire and Explosions Hazards	Isolate fire area and deny unnecessary entry. Fire fighters should wear positive-pressure self-contained breathing apparatus (SCBA) and protective clothing. Dust from machining and fabrication operations may be explosive if mixed with air in critical proportions in the presence of an ignition source. Heat from fire can generate decomposition products that may cause a health hazard.

Section 6. Accidental Release Measures

Small Spills	Contain and manage dust during manufacturing. If collected dust is spilled from collection container sweep up spilled material using water spray to suppress the dust. Shovel into suitable disposal container. Eliminate all ignition sources.
Large Spills	Eliminate all ignition sources. Sweep up spilled material using water spray to suppress dust. Transfer to proper containers for disposal. Persons not wearing protective equipment should be excluded from the area of spill until cleanup has been completed.

Section 7. Handling & Storage

Store material in a clean, cool, ventilated area away from all sources of ignition. Dust generated during normal manufacturing operations can represent both a health hazard and a fire hazard. Use dust control equipment at the point of generation in machining and sawing operations. Wash hands and other exposed areas thoroughly after handling and wash soiled clothing before reuse.

Section 8. Exposure Controls/Personal Exposure

Eye Protection	Minimize dust generating activities. Wear safety goggles with side shield or face shield. Contact lenses must not be worn.
Skin Protection	Wear gloves to protect against sharp edges and thermal effects when handling heated material. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.
Respiratory Protection	If personal exposure cannot be controlled below applicable limits by area ventilation, wear a properly fitted particulate respirator approved by NIOSH/MSHA for protection against dust. (See Section 2)
Ventilation	General area ventilation is acceptable if the exposure is maintained below applicable exposure limits. (See Section 2) Use local exhaust for sawing and machining operations.
Other Precautions	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

MATERIAL SAFETY DATA SHEET

Acculam™ Melaglas

Section 9. Physical and Chemical Properties

% Volatile Content by Weight	<0.05%	Specific Gravity (gm/cc)	1.7
Melting Point	N/A	Freezing Point (°C)	N/A
Vapor Pressure (mm Hg)	N/A	Solubility in Water	Insoluble
Vapor Density (Air=1)	N/A	Appearance and Odor	Grayish Brown Solid

Section 10. Stability and Reactivity

Stability	Stable
Conditions to Avoid	Protect from heat, sparks, flame and possible sources of ignition.
Incompatibility	Avoid contact with strong acids and bases
Hazardous Decomposition Products	Carbon dioxide, carbon monoxide, bromine and other hazardous gases. These gases and other volatiles may be generated under normal processing conditions.
Hazardous Polymerization	Will Not Occur!

Section 11. Toxicological Information (see Section 3. for Exposure Symptoms)

Acute Toxicity			
Component Tested	Oral LD ₅₀ (rat)	Dermal LD ₅₀ (rabbit)	Inhalation LC ₅₀ 4hr (rat)
Formaldehyde	500 mg/kg	270 mg/kg	203 mg/m ³
Glass Fiber (continuous filament)	N/D	N/D	N/D

N/D = Not Determined

Section 12. Ecological Information

Not biodegradable.

Section 13 Disposal Considerations

RCRA: This product, if disposed as shipped, is not considered a hazardous waste as specified in 40 CFR 261. Dispose of in accordance with all applicable federal, state and local regulations. Generation of particulates during machining and fabricating operations may be subject to Federal and State Air Pollution Control Laws.

Section 14 Transportation Information

This product, if offered for shipment, is not regulated by USDOT 49 CFR Parts 171 - 180: Regulation of Hazardous Materials Transportation in Commerce.	
Shipping Information	N/A
Classification	N/A
Identification	N/A
Packing Group	N/A
Label	N/A
NOT REGULATED AS HAZMAT	

Section 15. Regulatory Information

<i>Regulations Governing Product:</i>			
Inventory Status: United States (TSCA) - All ingredients are on the inventory or exempt from listing.			
SARA TITLE III			
EPCRA 302 EHS Extremely Hazardous Substance Reporting:		N/A	
EPCRA 311/312 Tier II Chemical Inventory Reporting:		N/A	
<i>Regulations Governing Ingredients</i> The reportable chemicals contained in these products are below De Minimis concentrations.			
Chemical Name	CAS #/Chemical Category	CERCLA RQ	SARA TITLE III EPCRA 313 RQ
N/A			

Section 16 Other Information

REFERENCES

CRC Press: Handbook of Chemical and Physical Constants by David R. Lide
Merck & Company: The Merck Index
Sigma-Aldrich Company: Aldrich Handbook of Fine Chemicals
Dictionary of Toxicology by Robert Lewis
National Library of Medicine TOXNET
US Department of Transportation, Research and Special Programs Administration: Hazardous Materials Table, Special Provisions, Hazardous Materials Communications, Emergency Response Information, and Training Requirements

The information contained herein are given in good faith but no guarantee or warranty of any kind, expressed or implied, is made with respect to the information above.

Accurate Plastics, Inc. expressly disclaims any liability which may be incurred in using the information contained herein.