



## Technical Specifications

### Product Description

The Nylon Toggle™ is made of resistant nylon with wings that expands behind the drywall. It is therefore rustproof and very economical. Sizes available are from 1/4" to 3/8". For a faster result and an easier way to install, try the NEW TripleGrip™ from Cobra.

### Features & Benefits

- ▶ For all type of material
- ▶ Corrosion resistant
- ▶ Available sizes: 1/4" and 3/8"
- ▶ Made of resistant engineered nylon

### Perfect for:



Bathroom applications, curtain rods, verticals, etc...

### Packaging:



## Nylon Toggle



### Product sizes & Materials

#### Nylon

1/4" X 1/4"  
1/4" X 3/8"  
1/4" X 1/2"  
3/8" X 3/8"  
3/8" X 1/2"  
3/8" X 5/8"

### Suitable Base Materials

- ▶ Wallboard 10 mm - Drywall 3/8
- ▶ Wallboard 13 mm - Drywall 1/2
- ▶ Wallboard 16 mm - Drywall 5/8
- ▶ Panelina



Masonry Anchors



### Load Capacities

### Nylon Toggle



Material	Size	Material	Drill Size	Grip Range	PULL MAX lbs	PULL SAFE lbs	SHEAR MAX lbs	SHEAR SAFE lbs	PULL MAX kg	PULL SAFE kg	SHEAR MAX kg	SHEAR SAFE kg
Drywall 3/8 Wallboard 10 mm	1/4" X 3/8"	Nylon	1/4"	5/16" - 7/16"	60	30	95	48	27	14	43	22
	3/8" X 3/8"	Nylon	3/8"	1/2" - 3/8"	84	42	150	75	38	19	68	34



Material	Size	Material	Drill Size	Grip Range	PULL MAX lbs	PULL SAFE lbs	SHEAR MAX lbs	SHEAR SAFE lbs	PULL MAX kg	PULL SAFE kg	SHEAR MAX kg	SHEAR SAFE kg
Drywall 1/2 Wallboard 13 mm	1/4" X 1/2"	Nylon	1/4"	7/16" - 9/16"	70	35	115	58	32	16	52	26
	3/8" X 1/2"	Nylon	3/8"	3/8" - 1/2"	115	58	200	100	52	26	91	45



Material	Size	Material	Drill Size	Grip Range	PULL MAX lbs	PULL SAFE lbs	SHEAR MAX lbs	SHEAR SAFE lbs	PULL MAX kg	PULL SAFE kg	SHEAR MAX kg	SHEAR SAFE kg
Drywall 5/8 Wallboard 16 mm	3/8" X 5/8"	Nylon	3/8"	1/2" - 5/8"	140	70	240	120	64	32	109	54



Material	Size	Material	Drill Size	Grip Range	PULL MAX lbs	PULL SAFE lbs	SHEAR MAX lbs	SHEAR SAFE lbs	PULL MAX kg	PULL SAFE kg	SHEAR MAX kg	SHEAR SAFE kg
Concrete 3000 PSI	1/4" X 1/4"	Nylon	1/4"	1/8" - 5/16"	85	43	200	100	39	19	91	45
	1/4" X 3/8"	Nylon	1/4"	5/16" - 7/16"	97	49	210	105	44	22	95	48
	1/4" X 1/2"	Nylon	1/4"	7/16" - 9/16"	110	55	220	110	50	25	100	50
	3/8" X 3/8"	Nylon	3/8"	1/2" - 3/8"	118	59	445	223	54	27	202	101
	3/8" X 1/2"	Nylon	3/8"	3/8" - 1/2"	157	79	576	288	71	36	261	131
	3/8" X 5/8"	Nylon	3/8"	1/2" - 5/8"	189	95	684	342	86	43	310	155



### Nylon Toggle



#### Tools required



#### Installation instructions

1. Drill an appropriate hole into the wall.
2. Fold the Nylon Toggle™ in 2 and insert in the hole.
3. Insert the screw through the object you need to affix.
4. Screw clockwise until firmly in place.

