

# Household Self-priming JET Pump



## JDW Series JETDP Series

**JETDP** pump comprises a ejector unit and a centrifugal pump. The most remarkable character is it can be used to supply clean water from a relatively deep well. It is also suitable for chemically non-aggressive fluid. To ensure the adequate counterpressure, it is always installed a foot valve with a filter on the suction opening.



- **Pump body:** Cast iron
- **Impeller:** Brass impeller
- **Motor:** Closed, externally ventilated
- **Insulation class:** B (Class F if required)
- **Protection class:** IP44 / IP54
- **Duty:** Continuously rated
- **Mechanical seal:**  $\phi 12$  ceramic  
steatite/graphite
- **Shaft:** Carbon steel AISI 1045 (Stainless  
steel AISI 420 if required)

The normal power standard is 220V 50Hz single phase.  
Three phase 220/380V/50Hz, 220/440V/60Hz,  
Single phase 230V, 240V, 127V, 110V, 115V/60Hz  
models are available on request.



### PERFORMANCE DATA

TYPE	Power		Ampere 1~220V	R.P.M	Ejector Type	Well Depth (m)	Capacity(l/min) At discharge head				Packing Size L×W×H(mm)	Weight NW(kg)
	HP	kW					10m	15m	25m	35m		
JDW-225 JETDP-225	0.5	0.37	3	2850	E20	10	50	34	12	-	420×300×230	16
					E20	15	34	20	5	-		
					E30	20	17	13	7	-		
JDW-370 JETDP-370	0.75	0.55	3.6		E20	10	-	42	18	15	420×300×230	17.4
					E20	15	-	25	16	10		
					E30	20	-	20	10	7		
JDW-505 JETDP-505	1	0.75	4.8		E20	15	-	38	24	28	420×300×230	18.2
					E30	20	-	30	17	15		
					E30	30	-	21	12	10		

